

Discreet & Easy to Install

Hidden discreetly within the frame of a door, the only visible part of the EV-DW4917 wireless recessed door transmitter once installed is the access cap (available in white or brown). Access caps are either flanged or non-flanged and allow for either a screw-mount or a press-fit installation. A flat head screwdriver is used to change the cap if needed or access the battery. Primarily designed for installation within a door, the transmitter can also be used within the frames of windows. The EV-DW4917 is built with reliable 433 MHz technology, is powered by a replaceable lithium battery and is compatible with all current DSC wireless receivers.



Product Features:

- ▶ Small, compact design
- ▶ Long-life lithium battery included
- ▶ Flexible mounting options (screw mount or press fit)
- ▶ Reliable 433 MHz technology
- ▶ Powerful, rare earth magnet
- ▶ Ships complete with flanged/non-flanged, brown/white access caps
- ▶ FCC/IC listed

Versatile

The EV-DW4917 is designed to provide installers with room for error during difficult installations. By having access caps flanged or non-flanged, installers are able to decide whether it's necessary to screw-mount or press-fit an installation. Another feature of this installer friendly transmitter is its replaceable lithium battery that provides uninterrupted supervised security for many years.

Inconspicuous and Unobtrusive

Barely discernable once installed, the EV-DW4917 is completely hidden when the door is closed. This is ideal for those customers who do not want to compromise the aesthetics of their décor.



Ordering Information:	
EV-DW4917	Wireless Recessed Door Transmitter (NA Baud Rate)

Compatibility

The EV-DW4917 is compatible with the following receivers:

PowerSeries™ Wireless Receivers
RF5132-433/PC5132-433 all versions and RF5108-433

MAXSYS® Wireless Receiver PC4164-433

PowerSeries RFK Keypads
(RFK5500/RFK5501/RFK5516/RFK5508)

Fixed-Message LCD Keypad with Integrated
Wireless Receiver RF5501-433

Envoy™ LCD Self-Contained Wireless Security
System NT9005

Specifications

- Dimensions 2 1/2" x 3/4" (64 mm x 19 mm)
- Battery CR2 (3 V Lithium)
- Battery Life 5-8 Years (Typical)
- Operating Temperature 0° to 49°C (32° to 120 °F)
- Operating Humidity 5-93% RH